



PM



## Round Tread Polyurethane on Aluminum Core



95 Shore A Models



80 Shore A Models

Composed of a polyurethane elastomer, open cast on clean, close tolerance cores. Wheels feature a chemical and mechanical lock of tread to the core. High capacity polyurethane protects floors, is non-marking and delivers quieter operation than standard metal wheels.

### FEATURES

- **Wheel face:** Round tread
- **Finish:** Green tread on aluminum core
- **Temperature Range:** -40°F to +180°F
- **Hardness:** 95 Shore A (green) or 80 Shore A (butterscotch)
- Wheels are complete with top hat and spacers

### WHEEL OPTIONS

- Available in **80 Shore A** and **70 Shore D**, consult factory.
- Note: Select bearings featured are recommended for standard applications. For special applications or alternate bearings consult factory. See bearing information on page 13
- For customization & special application options, please consult factory



Tread is mechanically and chemically bonded through a patented process to a lightweight durable aluminum core

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Hub Length (Inches)	Bore ID (Inches)	Bearing ID (Inches)	Approx. Wt. (Lbs)	Wheel Number Precision Ball (28)
<b>Round Tread Polyurethane on Aluminum Core (PM 95A)</b>							
5	2	1000	2-7/16	1-9/16	1/2	2	PM0522808
6	2	1250	2-7/16	1-9/16	1/2	3	PM0622808
8	2	1500	2-7/16	1-9/16	1/2	4	PM0822808

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Hub Length (Inches)	Bore ID (Inches)	Bearing ID (Inches)	Approx. Wt. (Lbs)	Wheel Number Precision Ball (28)
<b>Round Tread Polyurethane on Aluminum Core (PM 80A)</b>							
5	2	1000	2-7/16	1-9/16	1/2	2	PM052280880A
6	2	1250	2-7/16	1-9/16	1/2	3	PM062280880A
8	2	1500	2-7/16	1-9/16	1/2	4	PM082280880A

NEW

AX



## Round Tread Polyurethane on Aluminum Core



### Most Ergonomic Solution:

- Easiest movement
- Reduces noise
- Debris resistant
- Floor protective

Designed for ergonomic applications. Wheels feature a chemical and mechanical lock of tread to the core. High capacity polyurethane protects floors, is non-marking and delivers quieter operation than standard metal wheels.



### FEATURES

- **Wheel face:** Round tread
- **Finish:** Red tread on aluminum core
- **Temperature Range:** -40°F to +180°F
- **Hardness:** 85 Shore A
- Wheels are complete with top hat and spacers

### WHEEL OPTIONS

- For customization & special application options, please consult factory

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for manual operation)	Hub Length (Inches)	Bore ID (Inches)	Bearing ID (Inches)	Approx. Wt. (Lbs)	Wheel Number Precision Ball (28)
<b>Round Tread Polyurethane on Aluminum Core (AX)</b>							
4	2	800	2-7/16	1-9/16	1/2	1-1/2	AX0422808
5	2	1000	2-7/16	1-9/16	1/2	2	AX0522808
6	2	1250	2-7/16	1-9/16	1/2	3	AX0622808
8	2	1500	2-7/16	1-9/16	1/2	4	AX0822808