Access Casters (877) 881-6814









High Heat Glass Filled Nylon





Heat Resistant



Heavy Duty Glass Filled Nylon

Need tough, heat resistant wheels? Albion offers three versions: the RT, HT, and the newest addition to the family, the DT. These wheels are ideal for food processing, tool storage, sanitary maintenance, and applications requiring easy mobility under heavy loads. All three are extremely resistant to water, chemical absorption, steam cleaning, and HEAT!

FEATURES

- Wheel face: Moderate crown
- Finish: RT & HT (Black) DT (Dark Grey)
- Material:

RT: Glass filled polypropylene

HT: Glass filled nylon designed for higher temperature applications

DT: Heavy duty version of the RT wheels with regards to impact and load capacity and are made from a glass filled nylon with impact modifiers and temperature stabilization formulation

Temperature Range:

RT: -20°F to +250°F

HT: -20°F to +480°F

DT: -20°F to +350°F

Hardness:

RT: 65-70 Shore D

HT: 75-80 Shore D

DT: 75-80 Shore D

) /.l.	. / ō	/+	· / @	Agore ID		Wheel Number Precision Ball Bearing (28)	Wheel Number Pedestal Precision Ball Bearing (29)
Glass F	Glass Filled Polypropylene (RT)							
4	2	800	2-3/16	1-3/16	3/4	RT0420112		
4	2	800	2-3/16	1-3/16	1/2		RT0422808*	RT0422908
5	2	1000	2-3/16	1-3/16	3/4	RT0520112		
5	2	1000	2-3/16	1-3/16	1/2		RT0522808*	RT0522908
6	2	1200	2-3/16	1-3/16	3/4	RT0620112		
6	2	1200	2-3/16	1-3/16	1/2		RT0622808*	RT0622908
8	2	1400	2-3/16	1-3/16	3/4	RT0820112~		
8	2	1400	2-3/16	1-3/16	3/4		RT0822808*	RT0822908

^{*}Requires (2) top hats to achieve ½" ID; order (2) of part number 41774 for each wheel ordered.

High Heat Glass Filled Nylon (HT)									
4 2 800 2-3/16 1-3/16	3/4	HT0420112							
5 2 1000 2-3/16 1-3/16	3/4	HT0520112							
6 2 1200 2-3/16 1-3/16	3/4	HT0620112							
8 2 1400 2-3/16 1-3/16	3/4	HT0820112							

High temp Delrin bearing available, consult factory.

Heavy Duty Glass Filled Nylon (DT)									
4	2	1000	2-3/16 1-3/16	3/4	DT0420112				
4	2	800	2-3/16 1-3/16	1/2		DT0422808*	DT0422908		
5	2	1200	2-3/16 1-3/16	3/4	DT0520112				
5	2	1000	2-3/16 1-3/16	1/2		DT0522808*	DT0522908		
6	2	1400	2-3/16 1-3/16	3/4	DT0620112				
6	2	1200	2-3/16 1-3/16	1/2		DT0622808*	DT0622908		
8	2	1600	2-3/16 1-3/16	3/4	DT0820112				
8	2	1400	2-3/16 1-3/16	1/2		DT0822808*	DT0822908		

^{*}Requires (2) top hats to achieve $\frac{1}{2}$ " ID; order (2) of part number 41774 for each wheel ordered.

WHEEL OPTIONS

- Note: Select bearings featured are recommended for standard applications. For special applications or alternate bearings consult factory. See bearing information on page 13.
- For customization & special application options, please consult factory.
- For stainless steel roller bearing specify ZB03.

