

Thread Guard Casters

OPTIONAL ACCESSORIES *more help on page 13*

- **Wheel Brakes - Tread Contact (-CB)**
- **Swivel Lock – Field Installable (-4SL)**
– convert swivel to rigid for straight line steering
- **Sealed Swivel Assembly (-SS)**
– prolongs caster life in harsh environments
- **Wheel Bearing Seals (-BS)**
–for roller bearing wheels

This line of casters, with thread guards installed as standard equipment, provides improved availability for textile industry users requiring 1½" and 2" face wheels. The thread guards are metal or plastic discs fixed in place between the spanner bushing and caster leg to prevent loose threads from wrapping around the axle. Zinc plating is the standard caster finish. Lube-type axles with drilled spanner bushings are furnished on wheels with roller bearings.

WHEEL CHOICES *for more help, see pages 14 & 15*



★ = same day/next day **PRONTO®** shipment.

TG & TX Series Selection Table

Dia. A	Wheel			Swivel Caster		Rigid Caster		Load Cap. Lbs.	Overall Height B	Swivel Offset G
	Face	Type	Replacement Number	Hamilton Model No.	Wt. Lbs.	Hamilton Model No.	Wt. Lbs.			
4	1½	Aqualite®	W-415-AZ-¾	S-TX-4AZ	4	R-TX-4AZ	4	350	5½	1⅞
		Duralast®	W-41-D-¾	S-TX-4D	6	R-TX-4D	5	675		
		Metal	W-415-M-¾	S-TX-4M	7	R-TX-4M	6	550		
		Plastex	W-415-P-¾	S-TX-4P	5	R-TX-4P	4	600		
	2	Aqualite®	W-420-AZ-¾	S-TG-4AZ	5	R-TG-4AZ	4	550		
		Duralast®	W-420-DB-½	S-TG-4DB	8	R-TG-4DB	8	750		
		Metal	W-420-MB-½	S-TG-4MB	7	R-TG-4MB	7	900		
		Plastex	W-420-P-¾	S-TG-4P	6	R-TG-4P	5	800		
		Unilast™	W-420-UYB-½	S-TG-4UYB	6	R-TG-4UYB	5	750		
		Versa-Tech®	W-420-TE-¾	S-TG-4TE	5	R-TG-4TE	5	300		
5	1½	Aqualite®	W-515-AZ-¾	S-TX-5AZ	5	R-TX-5AZ	4	400	6½	1⅞
		Duralast®	W-515-D-¾	S-TX-5D	7	R-TX-5D	6	700		
		Metal	W-515-M-¾	S-TX-5M	7	R-TX-5M	6	750		
		Plastex	W-515-P-¾	S-TX-5P	6	R-TX-5P	5	600		
	2	Aqualite®	W-520-AZ-¾	S-TG-5AZ	5	R-TG-5AZ	5	650		
		Metal	W-520-MB-½	S-TG-5MB	9	R-TG-5MB	8	900		
		Plastex	W-520-P-¾	S-TG-5P	6	R-TG-5P	6	900		
		Poly-Tech®	W-520-NF-¾	S-TG-5NF	6	R-TG-5NF	5	900		
		Unilast™	W-520-UYB-½	S-TG-5UYB	6	R-TG-5UYB	5	900		
		Versa-Tech®	W-520-TE-¾	S-TG-5TE	6	R-TG-5TE	5	350		
		Vulcalite	W-520-AR-¾	S-TG-5AR	7	R-TG-5AR	6	350		
		Aqualite®	W-615-AZ-¾	S-TX-6AZ	5	R-TX-6AZ	5	525		
		Duralast®	W-61-D-¾	S-TX-6D	7	R-TX-6D	7	850		
		Metal	W-615-M-¾	S-TX-6M	10	R-TX-6M	10	850		
6	1½	Plastex	W-615-P-¾	S-TX-6P	6	R-TX-6P	6	800	7½	2⅞
		Aqualite®	W-620-AZ-¾	S-TG-6AZ	6	R-TG-6AZ	5	750		
		Duralast®	W-620-DB-½	S-TG-6DB	10	R-TG-6DB	10	900		
		Metal	W-620-MB-½	S-TG-6MB	10	R-TG-6MB	9	800		
	2	Plastex	W-620-P-¾	S-TG-6P	7	R-TG-6P	7	900		
		Polyplast	W-620-AY-¾	S-TG-6AY	7	R-TG-6AY	6	900		
		Poly-Tech®	W-620-NF-¾	S-TG-6NF	7	R-TG-6NF	6	900		
		Unilast®	W-620-UYB-½	S-TG-6UYB	7	R-TG-6UYB	6	900		
		Versa-Tech®	W-620-TE-¾	S-TG-6TE	6	R-TG-6TE	6	410		
		Vulcalite	W-620-AR-¾	S-TG-6AR	8	R-TG-6AR	7	410		
		Aqualite®	W-820-AZ-¾	S-TG-8AZ	7	R-TG-8AZ	6	900		
		Duralast®	W-820-DB-½	S-TG-8DB	13	R-TG-8DB	13	900		
		Metal	W-820-MB-½	S-TG-8MB	13	R-TG-8MB	12	900		
		Plastex	W-820-P-¾	S-TG-8P	9	R-TG-8P	8	900		
8	2	Polyplast	W-820-AY-¾	S-TG-8AY	7	R-TG-8AY	8	900	9½	2⅞
		Poly-Tech®	W-820-NF-¾	S-TG-8NF	8	R-TG-8NF	7	900		
		Unilast®	W-820-UYB-½	S-TG-8UYB	7	R-TG-8UYB	7	900		
		Versa-Tech®	W-820-TE-¾	S-TG-8TE	7	R-TG-8TE	6	500		
		Vulcalite	W-820-AR-¾	S-TG-8AR	11	R-TG-8AR	10	500		


* These wheels lubricated through lube axle.



#S-TG-6D
Swivel showing
Duralast® wheel

QUALITY FEATURES

Swivel Construction – formed steel mounting plate and horn base. Legs ¾" x 2" plate steel, formed and continuously welded to horn base.



Kingpin – permanent rivet-type, ⅝" dia.

Main and Secondary Load Bearings – hardened and polished steel balls rotate in two heat treated raceways.

Axle – ½" diameter hollow lube-type with lock nut.

Lube Fitting – to swivel assembly and to straight roller bearing wheels.

FEATURED WHEEL BEARINGS

