# L2-L9 Series

# **Light Duty**

Capacity to 75 pounds each

### **FEATURES**

- Finish: nickel plating to resist rust and corrosion.
- Swivel Construction: durable double ball raceway.
- ✓ Axle: 1/4" diameter.

### **CASTER OPTIONS**



**Brake:** available on quantity orders–consult factory.





Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Type	Bearing	Capacity (Pounds)	Round Stem Model Number	Load Height (Inches)	Swivel Radius (Inches)
2	13/16	CUSHION RUBBER	PLAIN	75	2-L2-201G	2 1/2	17/8
3		CUSHION RUBBER	PLAIN	75	3-L2-201G	3 1/2	29/16

Stem Size: For metal sockets 7/16" diameter x 1-29/32" long

# **L3 Spring Ring Stem**

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Type	Bearing	Capacity (Pounds)	Spring Ring Stem Model Number	Load Height (Inches)	Swivel Radius (Inches)
2	13/16	CUSHION RUBBER	PLAIN	75	2-L3-201G	2 1/2	17/8
3		CUSHION RUBBER	PLAIN	75	3-L3-201G	3 1/2	29/16

Stem Size: 7/16" diameter x 1-3/8" long

### **L4 Threaded Stem**

	Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Type	Bearing	Capacity (Pounds)	Threaded Stem Model Number	Load Height (Inches)	Swivel Radius (Inches)
1	2	13/16	CUSHION RUBBER	PLAIN	75	2-L4-201G	2 1/2	17/8
4	3		CUSHION RUBBER	PLAIN	75	3-L4-201G	3 1/2	29/16

**Stem Sizes:** to order, specify stem code number and add to end of caster model number (Example: 3-L4-201G **STEM1**)

**STEM 1:** 5/16" diameter – 18 x 3/4" long **STEM 3:** 3/8" diameter – 16 x 1-1/2" long

STEM 2: 3/8" diameter - 16 x 1" long

## **L5 Ladder Style Stem**

Wheel Diameter (Inches)	Tread Width (Inches)	Wheel Type	Bearing	Capacity (Pounds)	Ladder Style Model Number	Load Height (Inches)	Swivel Radius (Inches)
2	13/16	CUSHION BLACK RUBBER	PLAIN	75	2-L5-101	2 1/2	17/8
3		CUSHION BLACK RUBBER	PLAIN	75	3-L5-101	3 1/2	29/16

**Stem Size:** 5/16" diameter  $-18 \times 4-3/4$ " long with 5/8" thread length at top of stem; bottom stem flange is 9/16" diameter  $\times 1-13/16$ " long

# **L9 Swivel Top Plate**

Whe Diame (Inche	ter Width	Wheel Type	Bearing	Capacity (Pounds)	Swivel Top Plate Model Number	Load Height (Inches)	Swivel Radius (Inches)
2	13/16	CUSHION RUBBER	PLAIN	75	2-L9-201G	2 1/2	17/8
3	13/16	CUSHION RUBBER	PLAIN	75	3-L9-201G	3 1/2	29/16

Top Plate Size: 1-3/16" x 2" • Bolt Hole Spacing: 13/16" x 1-9/16" • Mounting Bolt Size: 3/16" diameter







Consult factory for brake option.