

HOSPITAL BED/STRETCHER REPLACEMENT WHEELS

new

35K THERMOPLASTIC RUBBER



- **Tread:** Grey TPE
- **Side:** Plastic Thread Guard
- **Hardness:** 80 (±5) Shore A

Wheel Diameter Inches (mm)	Tread Width Inches (mm)	Capacity (Lbs)	Bearing	Hub Width Inches (mm)	Bore Size Inches (mm)	Model Number
3.15" (80mm)	1-1/8" (30mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K080r
4" (100mm)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K100r
5" (125mm)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K125r
6" (150mm)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K150r
8" (200MM)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35k200r

35K ELECTRICALLY CONDUCTIVE THERMOPLASTIC RUBBER



- **Tread:** Grey TPE
- **Side:** Plastic Thread Guard
- **Hardness:** 80 (±5) Shore A

Wheel Diameter Inches (mm)	Tread Width Inches (mm)	Capacity (Lbs)	Bearing	Hub Width Inches (mm)	Bore Size Inches (mm)	Model Number
3.15" (80mm)	1-1/8" (30mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K080A
4" (100mm)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K100A
5" (125mm)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K125A

35K THERMOPLASTIC POLYURETHANE



- **Tread:** Grey TPE
- **Side:** Plastic Thread Guard
- **Hardness:** 90 (±5) Shore A

Wheel Diameter Inches (mm)	Tread Width Inches (mm)	Capacity (Lbs)	Bearing	Hub Width Inches (mm)	Bore Size Inches (mm)	Model Number
4" (100mm)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K100V
5" (125mm)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K125V
6" (150mm)	1-1/4" (32mm)	220	Precision Ball	1.44" (36.5mm)	5/16" (8mm)	35K150V

32C NATURAL SOLID RUBBER



- **Tread:** Blue/grey natural solid rubber molded on stamped steel rim
- **Side:** Metal Thread Guard
- **Hardness:** 80 (±5) Shore A

Wheel Diameter Inches (mm)	Tread Width Inches (mm)	Capacity (Lbs)	Bearing	Hub Width Inches (mm)	Bore Size Inches (mm)	Model Number
3.15" (80mm)	1-1/8" (30mm)	160	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C080bz
4" (100mm)	1-1/4" (32mm)	160	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C100bz
5" (125mm)	1-1/4" (32mm)	200	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C125bz
6" (150mm)	1-1/4" (32mm)	220	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C150bz
8" (200MM)	1-1/4" (32mm)	240	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C200bz

32C ELECTRICALLY CONDUCTIVE NATURAL SOLID RUBBER



- **Tread:** Black natural solid rubber molded on stamped steel rim
- **Side:** Metal Thread Guard
- **Hardness:** 80 (±5) Shore A

Wheel Diameter Inches (mm)	Tread Width Inches (mm)	Capacity (Lbs)	Bearing	Hub Width Inches (mm)	Bore Size Inches (mm)	Model Number
3.15" (80mm)	1-1/8" (30mm)	160	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C080az
4" (100mm)	1-1/4" (32mm)	160	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C100az
5" (125mm)	1-1/4" (32mm)	200	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C125az
6" (150mm)	1-1/4" (32mm)	220	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32c150az
8" (200MM)	1-1/4" (32mm)	240	Flanged Ball	1.46" (37mm)	5/16" (8mm)	32C200az