# Stainless Steel (SS)

## Top Plate Models

Free Swivel • Total Lock • Direction Lock
1-1/4 Tread Width

### Applications

- Food Service
- Case Carts
- Utility Carts
- Medical Equipment
- Institutional Equipment
- Laboratory Equipment
- Animal Cages
- Pharmecutical Equipment

### Features

- 304 Stainless Steel, Polished
- Dual Ball Swivel Raceways for added strength
- **Total Lock Brake** models lock both swivel and wheel
- Directional lock models lock swivel only (helps with Steering)
- Precison ball bearings in wheels for easier rollability
- Wheels have full plastic thread guards for added protection
- TPP and AMP wheels are crowned for easy rolling and turning

Our SS series design is constructed of stainless steel. This design gives you the quality necessary for most medical and pharmaceutical applications at an affordable price.

## Swivel Top Plate Models

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-7/16" (113) | 2-29/32" (74) | Annular Ball | SS-03CRB-125-SW-TP01 |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-7/16" (113) | 2-29/32" (74) | Precision Ball | SS-03TPP-125-SW-TP01 |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-7/16" (113) | 2-29/32" (74) | Precision Ball | SS-03AMP-125-SW-TP01 |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-7/16" (113) | 2-29/32" (74) | Precision Ball | SS-03PYP-125-SW-TP01 |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-7/16" (138) | 3-37/64" (91) | Annular Ball | SS-04CRB-125-SW-TP01 |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-7/16" (138) | 3-37/64" (91) | Precision Ball | SS-04TPP-125-SW-TP01 |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-7/16" (138) | 3-37/64" (91) | Precision Ball | SS-04AMP-125-SW-TP01 |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-7/16" (138) | 3-37/64" (91) | Precision Ball | SS-04PYP-125-SW-TP01 |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-7/16" (163) | 4-7/32" (108) | Annular Ball | SS-05CRB-125-SW-TP01 |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-7/16" (163) | 4-7/32" (108) | Precision Ball | SS-05TPP-125-SW-TP01 |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-7/16" (163) | 4-7/32" (108) | Precision Ball | SS-05AMP-125-SW-TP01 |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-7/16" (163) | 4-7/32" (108) | Precision Ball | SS-05PYP-125-SW-TP01 |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-13/32" (188) | 4-39/64 (117) | Annular Ball | SS-06CRB-125-SW-TP01 |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-13/32" (188) | 4-39/64 (117) | Precision Ball | SS-06TPP-125-SW-TP01 |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-13/32" (188) | 4-39/64 (117) | Precision Ball | SS-06AMP-125-SW-TP01 |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-13/32" (188) | 4-39/64 (117) | Precision Ball | SS-06PYP-125-SW-TP01 |

Rigid models available change "SW to "RG"

## Top Plate Fitting

Swivel Top Plate Pattern

TP01




*Anti-Microbial wheels have light green tread.*

**Other Wheel Bearing Options**
**Stainless steel:** Change bearing code to "X"
(Example : SS-03PY**X**-125-SW-TP01)

**NEW** **Delrin:** Change bearing code to "N"
(Example : SS-03TP**N**-125-SW-TP01)



www.accesscasters.com

# Stainless Steel (SS)

## Swivel Top Plate Total Lock Models
(Locks Wheel and Swivel)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-7/16" (113) | 4-1/4" (108) | Annular Ball | SS-03CRB-125-TL-TP01 |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-7/16" (113) | 4-1/4" (108) | Precision Ball | SS-03TPP-125-TL-TP01 |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-7/16" (113) | 4-1/4" (108) | Precision Ball | SS-03AMP-125-TL-TP01 |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-7/16" (113) | 4-1/4" (108) | Precision Ball | SS-03PYP-125-TL-TP01 |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-7/16" (138) | 4-35/64" (115) | Annular Ball | SS-04CRB-125-TL-TP01 |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-7/16" (138) | 4-35/64" (115) | Precision Ball | SS-04TPP-125-TL-TP01 |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-7/16" (138) | 4-35/64" (115) | Precision Ball | SS-04AMP-125-TL-TP01 |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-7/16" (138) | 4-35/64" (115) | Precision Ball | SS-04PYP-125-TL-TP01 |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-7/16" (163) | 4-55/64" (123) | Annular Ball | SS-05CRB-125-TL-TP01 |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-7/16" (163) | 4-55/64" (123) | Precision Ball | SS-05TPP-125-TL-TP01 |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-7/16" (163) | 4-55/64" (123) | Precision Ball | SS-05AMP-125-TL-TP01 |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-7/16" (163) | 4-55/64" (123) | Precision Ball | SS-05PYP-125-TL-TP01 |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-13/32" (188) | 4-55/64" (123) | Annular Ball | SS-06CRB-125-TL-TP01 |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-13/32" (188) | 4-55/64" (123) | Precision Ball | SS-06TPP-125-TL-TP01 |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-13/32" (188) | 4-55/64" (123) | Precision Ball | SS-06AMP-125-TL-TP01 |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-13/32" (188) | 4-55/64" (123) | Precision Ball | SS-06PYP-125-TL-TP01 |

**Total Lock**
Change "SW" to "TL". Red sticker on pedal.

## Swivel Top Plate Direction Lock Models
(Locks Swivel Only)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-7/16" (113) | 4-1/4" (108) | Annular Ball | SS-03CRB-125-DL-TP01 |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-7/16" (113) | 4-1/4" (108) | Precision Ball | SS-03TPP-125-DL-TP01 |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-7/16" (113) | 4-1/4" (108) | Precision Ball | SS-03AMP-125-DL-TP01 |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-7/16" (113) | 4-1/4" (108) | Precision Ball | SS-03PYP-125-DL-TP01 |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-7/16" (138) | 4-35/64" (115) | Annular Ball | SS-04CRB-125-DL-TP01 |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-7/16" (138) | 4-35/64" (115) | Precision Ball | SS-04TPP-125-DL-TP01 |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-7/16" (138) | 4-35/64" (115) | Precision Ball | SS-04AMP-125-DL-TP01 |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-7/16" (138) | 4-35/64" (115) | Precision Ball | SS-04PYP-125-DL-TP01 |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-7/16" (163) | 4-55/64" (123) | Annular Ball | SS-05CRB-125-DL-TP01 |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-7/16" (163) | 4-55/64" (123) | Precision Ball | SS-05TPP-125-DL-TP01 |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-7/16" (163) | 4-55/64" (123) | Precision Ball | SS-05AMP-125-DL-TP01 |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-7/16" (163) | 4-55/64" (123) | Precision Ball | SS-05PYP-125-DL-TP01 |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-13/32" (188) | 4-55/64" (123) | Annular Ball | SS-06CRB-125-DL-TP01 |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-13/32" (188) | 4-55/64" (123) | Precision Ball | SS-06TPP-125-DL-TP01 |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-13/32" (188) | 4-55/64" (123) | Precision Ball | SS-06AMP-125-DL-TP01 |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-13/32" (188) | 4-55/64" (123) | Precision Ball | SS-06PYP-125-DL-TP01 |

**Direction Lock**
Change "SW" to "DL". Green sticker on pedal.

## Top Plate Fitting

Swivel Top Plate Pattern

TP01




**Other Wheel Bearing Options**
**Stainless steel:** Change bearing code to "X"
(Example : SS-03PY**X**-125-SW-TP01)

**NEW Delrin:** Change bearing code to "N"
(Example : SS-03TP**N**-125-SW-TP01)

www.accessscasters.com

# Stainless Steel (SS)

## Hollow Kingpin Models

Free Swivel • Total Lock • Direction Lock
1-1/4 Tread Width

### Applications

- Food Service
- Case Carts
- Utility Carts
- Medical Equipment
- Institutional Equipment
- Laboratory Equipment
- Animal Cages
- Pharmecutical Equipment

### Features

- 304 Stainless Steel, Polished
- Dual Ball Swivel Raceways for added strength
- **Total Lock Brake** models lock both swivel and wheel
- Directional lock models lock swivel only (helps with Steering)
- Precison ball bearings in wheels for easier rollability
- Wheels have full plastic thread guards for added protection
- TPP and AMP wheels are crowned for easy rolling and turning

Our SS series design is constructed of stainless steel. This design gives you the quality necessary for most medical and pharmaceutical applications at an affordable price.

## Hollow Kingpin Models

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-5/16" (109) | 2-29/32" (74) | Annular Ball | SS-03CRB-125-SW-HKU1 |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-5/16" (109) | 2-29/32" (74) | Precision Ball | SS-03TPP-125-SW-HKU1 |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-5/16" (109) | 2-29/32" (74) | Precision Ball | SS-03AMP-125-SW-HKU1 |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-5/16" (109) | 2-29/32" (74) | Precision Ball | SS-03PYP-125-SW-HKU1 |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-5/16" (135) | 3-37/64" (91) | Annular Ball | SS-04CRB-125-SW-HKU1 |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-5/16" (135) | 3-37/64" (91) | Precision Ball | SS-04TPP-125-SW-HKU1 |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-5/16" (135) | 3-37/64" (91) | Precision Ball | SS-04AMP-125-SW-HKU1 |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-5/16" (135) | 3-37/64" (91) | Precision Ball | SS-04PYP-125-SW-HKU1 |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-5/16" (160) | 4-7/32" (108) | Annular Ball | SS-05CRB-125-SW-HKU1 |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-5/16" (160) | 4-7/32" (108) | Precision Ball | SS-05TPP-125-SW-HKU1 |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-5/16" (160) | 4-7/32" (108) | Precision Ball | SS-05AMP-125-SW-HKU1 |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-5/16" (160) | 4-7/32" (108) | Precision Ball | SS-05PYP-125-SW-HKU1 |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-9/32" (185) | 4-39/64 (117) | Annular Ball | SS-06CRB-125-SW-HKU1 |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-9/32" (185) | 4-39/64 (117) | Precision Ball | SS-06TPP-125-SW-HKU1 |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-9/32" (185) | 4-39/64 (117) | Precision Ball | SS-06AMP-125-SW-HKU1 |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-9/32" (185) | 4-39/64 (117) | Precision Ball | SS-06PYP-125-SW-HKU1 |

*Anti-Microbial wheels have light green tread.*

### Hollow Kingpin

Caster is **provided unassembled** to make it easy to add your choice of fitting. If you would like these assembled change **HKU1** to **HK01**. 1/2 I.D.

**Other Wheel Bearing Options**
**Stainless steel:** Change bearing code to "X" (Example : SS-03PY**X**-125-SW-HKU1)
**NEW** **Delrin:** Change bearing code to "N" (Example : SS-03TP**N**-125-SW-HKU1)



www.accesscasters.com

Access Casters (877) 881-6814

# Stainless Steel (SS)

## Hollow Kingpin Total Lock Models
(Locks Wheel and Swivel)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-5/16" (109) | 4-1/4" (108) | Annular Ball | SS-03CRB-125-TL-HKU1 |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03TPP-125-TL-HKU1 |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03AMP-125-TL-HKU1 |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03PYP-125-TL-HKU1 |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-5/16" (135) | 4-35/64" (115) | Annular Ball | SS-04CRB-125-TL-HKU1 |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04TPP-125-TL-HKU1 |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04AMP-125-TL-HKU1 |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04PYP-125-TL-HKU1 |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-5/16" (160) | 4-55/64" (123) | Annular Ball | SS-05CRB-125-TL-HKU1 |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05TPP-125-TL-HKU1 |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05AMP-125-TL-HKU1 |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05PYP-125-TL-HKU1 |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-9/32" (185) | 4-55/64" (123) | Annular Ball | SS-06CRB-125-TL-HKU1 |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06TPP-125-TL-HKU1 |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06AMP-125-TL-HKU1 |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06PYP-125-TL-HKU1 |

**Total Lock**
Change "SW" to "TL". Red sticker on pedal.

## Hollow Kingpin Direction Lock Models
(Locks Swivel Only)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-5/16" (109) | 4-1/4" (108) | Annular Ball | SS-03CRB-125-DL-HKU1 |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03TPP-125-DL-HKU1 |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03AMP-125-DL-HKU1 |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03PYP-125-DL-HKU1 |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-5/16" (135) | 4-35/64" (115) | Annular Ball | SS-04CRB-125-DL-HKU1 |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04TPP-125-DL-HKU1 |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04AMP-125-DL-HKU1 |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04PYP-125-DL-HKU1 |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-5/16" (160) | 4-55/64" (123) | Annular Ball | SS-05CRB-125-DL-HKU1 |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05TPP-125-DL-HKU1 |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05AMP-125-DL-HKU1 |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05PYP-125-DL-HKU1 |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-9/32" (185) | 4-55/64" (123) | Annular Ball | SS-06CRB-125-DL-HKU1 |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06TPP-125-DL-HKU1 |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06AMP-125-DL-HKU1 |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06PYP-125-DL-HKU1 |

**Direction Lock**
Change "SW" to "DL". Green sticker on pedal.

## Hollow Kingpin

Caster is **provided unassembled** to make it easy to add your choice of fitting. If you would like these assembled change **HKU1** to **HK01**. 1/2 I.D.

**Other Wheel Bearing Options**
**Stainless steel:** Change bearing code to "X" (Example : SS-03PY**X**-125-SW-HKU1)

**NEW** **Delrin:** Change bearing code to "N" (Example : SS-03TP**N**-125-SW-HKU1)



Access Casters (877) 881-6814

www.accesscasters.com

# Stainless Steel (SS)

## Stem Models

Free Swivel • Total Lock • Direction Lock
1-1/4 Tread Width

**Applications**

- Food Service
- Case Carts
- Utility Carts
- Medical Equipment
- Institutional Equipment
- Laboratory Equipment
- Animal Cages
- Pharmecutical Equipment

**Features**

- 304 Stainless Steel, Polished
- Dual Ball Swivel Raceways for added strength
- **Total Lock Brake** models lock both swivel and wheel
- Directional lock models lock swivel only (helps with Steering)
- Precison ball bearings in wheels for easier rollability
- Wheels have full plastic thread guards for added protection
- TPP and AMP wheels are crowned for easy rolling and turning

Our SS series design is constructed of stainless steel. This design gives you the quality necessary for most medical and pharmaceutical applications at an affordable price.

## Stem Models

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-5/16" (109) | 2-29/32" (74) | Annular Ball | SS-03CRB-125-SW-____ |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-5/16" (109) | 2-29/32" (74) | Precision Ball | SS-03TPP-125-SW-____ |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-5/16" (109) | 2-29/32" (74) | Precision Ball | SS-03AMP-125-SW-____ |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-5/16" (109) | 2-29/32" (74) | Precision Ball | SS-03PYP-125-SW-____ |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-5/16" (135) | 3-37/64" (91) | Annular Ball | SS-04CRB-125-SW-____ |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-5/16" (135) | 3-37/64" (91) | Precision Ball | SS-04TPP-125-SW-____ |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-5/16" (135) | 3-37/64" (91) | Precision Ball | SS-04AMP-125-SW-____ |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-5/16" (135) | 3-37/64" (91) | Precision Ball | SS-04PYP-125-SW-____ |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-5/16" (160) | 4-7/32" (108) | Annular Ball | SS-05CRB-125-SW-____ |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-5/16" (160) | 4-7/32" (108) | Precision Ball | SS-05TPP-125-SW-____ |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-5/16" (160) | 4-7/32" (108) | Precision Ball | SS-05AMP-125-SW-____ |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-5/16" (160) | 4-7/32" (108) | Precision Ball | SS-05PYP-125-SW-____ |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-9/32" (185) | 4-39/64 (117) | Annular Ball | SS-06CRB-125-SW-____ |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-9/32" (185) | 4-39/64 (117) | Precision Ball | SS-06TPP-125-SW-____ |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-9/32" (185) | 4-39/64 (117) | Precision Ball | SS-06AMP-125-SW-____ |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-9/32" (185) | 4-39/64 (117) | Precision Ball | SS-06PYP-125-SW-____ |

*Anti-Microbial wheels have light green tread.*

## Stem Fittings

See fittings page for more options.

Threaded Stems

**TS12**

**TS13**




**TS14**




Grip Ring Stem

**GRS2**




**Other Wheel Bearing Options**
**Stainless steel:** Change bearing code to "X"
(Example : SS-03PY**X**-125-SW-TS12)

**NEW** **Delrin:** Change bearing code to "N"
(Example : SS-03TP**N**-125-SW-TS12)

Round and square stems available, please consult factory.



www.accesscasters.com

Access Casters (877) 881-6814

# Stainless Steel (SS)

## Stem Total Lock Models
(Locks Wheel and Swivel)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-5/16" (109) | 4-1/4" (108) | Annular Ball | SS-03CRB-125-TL-____ |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03TPP-125-TL-____ |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03AMP-125-TL-____ |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03PYP-125-TL-____ |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-5/16" (135) | 4-35/64" (115) | Annular Ball | SS-04CRB-125-TL-____ |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04TPP-125-TL-____ |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04AMP-125-TL-____ |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04PYP-125-TL-____ |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-5/16" (160) | 4-55/64" (123) | Annular Ball | SS-05CRB-125-TL-____ |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05TPP-125-TL-____ |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05AMP-125-TL-____ |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05PYP-125-TL-____ |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-9/32" (185) | 4-55/64" (123) | Annular Ball | SS-06CRB-125-TL-____ |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06TPP-125-TL-____ |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06AMP-125-TL-____ |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06PYP-125-TL-____ |

**Total Lock**
Change "SW" to "TL". Red sticker on pedal.

## Stem Direction Lock Models
(Locks Swivel Only)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|---|---|---|---|---|---|---|---|
| 3 | 1-1/4 | Conductive Rubber | 165 | 4-5/16" (109) | 4-1/4" (108) | Annular Ball | SS-03CRB-125-DL-____ |
| 3 | 1-1/4 | Thermoplastic Rubber | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03TPP-125-DL-____ |
| 3 | 1-1/4 | Anti-Microbial TPR | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03AMP-125-DL-____ |
| 3 | 1-1/4 | Polyurethane TPU | 165 | 4-5/16" (109) | 4-1/4" (108) | Precision Ball | SS-03PYP-125-DL-____ |
| 4 | 1-1/4 | Conductive Rubber | 190 | 5-5/16" (135) | 4-35/64" (115) | Annular Ball | SS-04CRB-125-DL-____ |
| 4 | 1-1/4 | Thermoplastic Rubber | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04TPP-125-DL-____ |
| 4 | 1-1/4 | Anti-Microbial TPR | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04AMP-125-DL-____ |
| 4 | 1-1/4 | Polyurethane TPU | 190 | 5-5/16" (135) | 4-35/64" (115) | Precision Ball | SS-04PYP-125-DL-____ |
| 5 | 1-1/4 | Conductive Rubber | 220 | 6-5/16" (160) | 4-55/64" (123) | Annular Ball | SS-05CRB-125-DL-____ |
| 5 | 1-1/4 | Thermoplastic Rubber | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05TPP-125-DL-____ |
| 5 | 1-1/4 | Anti-Microbial TPR | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05AMP-125-DL-____ |
| 5 | 1-1/4 | Polyurethane TPU | 220 | 6-5/16" (160) | 4-55/64" (123) | Precision Ball | SS-05PYP-125-DL-____ |
| 6 | 1-1/4 | Conductive Rubber | 240 | 7-9/32" (185) | 4-55/64" (123) | Annular Ball | SS-06CRB-125-DL-____ |
| 6 | 1-1/4 | Thermoplastic Rubber | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06TPP-125-DL-____ |
| 6 | 1-1/4 | Anti-Microbial TPR | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06AMP-125-DL-____ |
| 6 | 1-1/4 | Polyurethane TPU | 240 | 7-9/32" (185) | 4-55/64" (123) | Precision Ball | SS-06PYP-125-DL-____ |

**Direction Lock**
Change "SW" to "DL". Green sticker on pedal.

Stems ship with a loose bolt for easier alignment of the directional lock. The direction lock caster will not remain in a fixed position when used with a grip ring stem.

Specify code, see fittings at left for dimensions.

## Stem Fittings

See fittings page for more options.

Threaded Stems

**TS12**
1" 13NC
1/2"

**TS13**
1-1/2" 13NC
1/2"

**TS14**
2" 13NC
1/2"

Grip Ring Stem

**GRS2**
1-7/16"
7/16"
(Stainless steel)

Round and square stems available, please consult factory.

**Other Wheel Bearing Options**
**Stainless steel:** Change bearing code to "X"
(Example : SS-03PY**X**-125-SW-TS12)
**NEW Delrin:** Change bearing code to "N"
(Example : SS-03TP**N**-125-SW-TS12)



Access Casters (877) 881-6814

www.accesscasters.com