

STAINLESS STEEL (SS)

TOP PLATE MODELS

FREE SWIVEL • TOTAL LOCK
2" TREAD WIDTH



New Total Lock brake design – locks both brake and swivel.

Eagle Polyurethane wheels now available

APPLICATIONS

- Food Service
- Case Carts
- Utility Carts
- Medical Equipment
- Institutional Equipment
- Laboratory Equipment
- Animal Cages
- Pharmaceutical Equipment

FEATURES

- Fork legs, top plate and yoke base are made of 1/4" thick 304 polished stainless steel for added corrosion protection
- **Total Lock brake** models lock both brake and swivel
- Dual Ball Swivel Raceways for added strength
- Swivel seals are standard for added protection
- Stainless axles provided with grease fitting
- Grease fitting in swivel raceway

Our SS series design is constructed of stainless steel. This design gives you the quality necessary for most medical and pharmaceutical applications at an affordable price.


Stainless Steel
Top Lock Brake
(Change SW to TB)

Example :

SS-06PSR-200-TB-TP03



TOP PLATE FITTING



STAINLESS STEEL TOP LOCK BRAKE

| Wheel Diameter | Kit Number |
|----------------|------------|
| 4" | SS04200 |
| 5" | SS05200 |
| 6" | SS06200 |
| 8" | SS08200 |



To order field installable kit specify kit number.
To order on caster change fork code from "SW" to "TB"

(Example:
SS-06PSR-200-TB-TP03)



STAINLESS STEEL (SS)

TOP PLATE MODELS

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height (Inches) | Swivel Radius (Inches) | Wheel Bearing | Model Number |
|-------------------------|----------------------|--------------------|----------------|----------------------|------------------------|---------------|----------------------|
| 4 | 2 | White Polyolefin | 550 | 5-5/8 | 3-3/8 | Delrin | SS-04PWD-200-SW-TP03 |
| 4 | 2 | White Polyolefin | 550 | 5-5/8 | 3-3/8 | Roller | SS-04PWR-200-SW-TP03 |
| 4 | 2 | Polyurethane Eagle | 600 | 5-5/8 | 3-3/8 | Delrin | SS-04EPD-200-SW-TP03 |
| 4 | 2 | Polyurethane Eagle | 600 | 5-5/8 | 3-3/8 | Roller | SS-04EPR-200-SW-TP03 |
| 4 | 2 | Polyurethane Solid | 800 | 5-5/8 | 3-3/8 | Roller | SS-04PSR-200-SW-TP03 |
| 4 | 2 | Polyurethane Solid | 800 | 5-5/8 | 3-3/8 | Delrin | SS-04PSD-200-SW-TP03 |
| 5 | 2 | White Polyolefin | 650 | 6-1/2 | 4-1/8 | Delrin | SS-05PWD-200-SW-TP03 |
| 5 | 2 | White Polyolefin | 650 | 6-1/2 | 4-1/8 | Roller | SS-05PWR-200-SW-TP03 |
| 5 | 2 | Polyurethane Eagle | 900 | 6-1/2 | 4-1/8 | Delrin | SS-05EPD-200-SW-TP03 |
| 5 | 2 | Polyurethane Eagle | 900 | 6-1/2 | 4-1/8 | Roller | SS-05EPR-200-SW-TP03 |
| 5 | 2 | Polyurethane Solid | 900 | 6-1/2 | 4-1/8 | Roller | SS-05PSR-200-SW-TP03 |
| 5 | 2 | Polyurethane Solid | 900 | 6-1/2 | 4-1/8 | Delrin | SS-05PSD-200-SW-TP03 |
| 6 | 2 | White Polyolefin | 700 | 7-1/2 | 4-3/4 | Delrin | SS-06PWD-200-SW-TP03 |
| 6 | 2 | White Polyolefin | 700 | 7-1/2 | 4-3/4 | Roller | SS-06PWR-200-SW-TP03 |
| 6 | 2 | Polyurethane Solid | 900 | 7-1/2 | 4-3/4 | Roller | SS-06PSR-200-SW-TP03 |
| 6 | 2 | Polyurethane Solid | 900 | 7-1/2 | 4-3/4 | Delrin | SS-06PSD-200-SW-TP03 |
| 6 | 2 | Polyurethane Eagle | 1000 | 7-1/2 | 4-3/4 | Delrin | SS-06EPD-200-SW-TP03 |
| 6 | 2 | Polyurethane Eagle | 1000 | 7-1/2 | 4-3/4 | Roller | SS-06EPR-200-SW-TP03 |
| 8 | 2 | White Polyolefin | 800 | 9-1/2 | 5-3/4 | Delrin | SS-08PWD-200-SW-TP03 |
| 8 | 2 | White Polyolefin | 800 | 9-1/2 | 5-3/4 | Roller | SS-08PWR-200-SW-TP03 |
| 8 | 2 | Polyurethane Solid | 900 | 9-1/2 | 5-3/4 | Roller | SS-08PSR-200-SW-TP03 |
| 8 | 2 | Polyurethane Solid | 900 | 9-1/2 | 5-3/4 | Delrin | SS-08PSD-200-SW-TP03 |
| 8 | 2 | Polyurethane Eagle | 1000 | 9-1/2 | 5-3/4 | Delrin | SS-08EPD-200-SW-TP03 |
| 8 | 2 | Polyurethane Eagle | 1000 | 9-1/2 | 5-3/4 | Roller | SS-08EPR-200-SW-TP03 |



Stainless Steel Roller Bearings available, change bearing designation to S, example SS-08PWS200-SW-TP03.

Stainless Steel Precision Bearings available on some models, please consult factory.


Other bearings also available, please consult factory.

Stainless wheel brakes are available for swivel models, Change SW to TB.

Rigid models are available, change SW to RG.

Stainless Steel **Total Lock** brake available for swivel models, change SW to TL.

TOP PLATE FITTING



Total Lock Swivel Lead/Swivel Radius

| Part Number | Swivel Lead | Swivel Radius |
|----------------|-------------|---------------|
| SS04200TL-TP03 | 34.0 mm | 150.6 mm |
| SS05200TL-TP03 | 38.2 mm | 160.5 mm |
| SS06200TL-TP03 | 44.3 mm | 170.8 mm |
| SS08200TL-TP03 | 56.0 mm | 193.5 mm |

