

# S65 STAINLESS STEEL CASTERS

RWM Caster's S65 Stainless Steel Casters are ideally suited for frequent washdown applications. This industrial strength caster can handle cleaning agents, steam, caustic solutions or other corrosive agents that can cause rust or corrosion. These industrial casters are proudly made in the USA. The S65 Stainless Steel kingpinless casters are constructed of high quality 304 stainless steel for the best possible corrosion performance attributes.




S65-GTB-0620-S-EP

## FEATURES

<b>Raceway Design</b>	Patented Kingpinless™ single ball bearing precision machined raceway. 2-3/8" diameter raceway with 3/8" stainless ball bearings.
<b>Capacity</b>	Up to 1200 lbs.
<b>Axle</b>	1/2" bolt with locking nut
<b>Leg Thickness</b>	3/16"
<b>Wheels</b>	Wheels are available with either a straight roller bearing, an annular ball bearing for ease of rollability, or a celcon bearing
<b>Mounting Plate Size</b>	4" x 4-1/2" x 1/4"
<b>Bolt Hole Spacing</b>	2-5/8" x 3-5/8" slotted to 3" x 3"
<b>Mounting Bolt Diameter</b>	3/8"

## RACEWAY




## APPLICATIONS


RWM's Stainless Steel Casters feature surgical grade 304 stainless steel that is highly resistant to conditions that would normally corrode and rust regular zinc plated steel casters. Our Stainless Steel Casters are ideal for wet or damp conditions and harsh environments that may rust or corrode standard zinc casters.

Food processing plants	Seafood processing plants
Food service equipment	Stock and maintenance carts
Large volume, high temperature bakery and food cooking facilities	Ingredient bins
Bakery and bread racks	Institutional service carts and equipment
Slaughter houses	Hatcheries
Fisheries	Pharmaceutical plants and laboratories


### STANDARD




### 41ST/RT



### 42ST/RT



### 43ST/RT



## OPTIONS

### BRAKES

- SICWB** Stainless Installable Face Contact Brake
- SCWB** Stainless Steel Cam Wheel Brake
- WB** Stainless Side Wheel Brake (Roller Bearing Only)

### SWIVEL LOCKS

- DSL** Demountable Swivel Lock STD TP Only
- SL** Swivel Lock

### BEARINGS

- SSBB** Stainless Steel Ball Bearing
- SSRB** Stainless Steel Roller Bearing

### FINISHES

- EP** Electropolished Finish

### RACEWAYS

- SR** Sealed Swivel Raceway

## OPTIONAL OVERALL HEIGHTS

Wheel Diameter	Overall Height
4"	5-9/16"
5"	6-11/16"
6"	7-5/8"
8"	9-1/2"

CASTERS

STAINLESS STEEL

ENGINEERED TO OUTPERFORM

UP TO 1,200 LBS CAPACITY

Wheel Diameter	Wheel Width	Capacity lbs.	Wheel Type	Overall Height	Swivel Caster Model Numbers			Swivel Lead	Approx Weight lbs.
					Roller Bearing	Ball Bearing	Plain Bearing		
4"	2"	350	Performance TPR	5-5/8"	S65-RPR-0420-S	S65-RPB-0420-S	S65-RPC-0420-S	1-1/4"	7.3
		400	Signature	5-5/8"		S65-SWB-0420-S		1-1/4"	7
		500	Polyolefin	5-5/8"	S65-POR-0420-S	S65-POB-0420-S	S65-POC-0420-S	1-1/4"	7.6
		600	Urethane Polypropylene	5-5/8"	S65-UPR-0420-S	S65-UPB-0420-S	S65-UPC-0420-S	1-1/4"	7.3
		700	Rubber on Aluminum-EHT	5-5/8"		S65-RAB-0420-S-EHT		1-1/4"	8
		700	Solid Urethane	5-5/8"		S65-MUB-0420-S		1-1/4"	8
		700	Urethane on Aluminum	5-5/8"	S65-UAR-0420-S		S65-UAC-0420-S	1-1/4"	7.5
		700	Urethane on Iron	5-5/8"	S65-UIR-0420-S	S65-UIB-0420-S	S65-UIC-0420-S	1-1/4"	8
		800	Durastan	5-5/8"	S65-DUR-0420-S	S65-DUB-0420-S	S65-DUC-0420-S	1-1/4"	8
		800	High Temp. Nylon	5-5/8"	S65-HNR-0420-S			1-1/4"	8
		1050	GT	5-5/8"		S65-GTB-0420-S		1-1/4"	8
5"	2"	375	Performance TPR	6-1/2"	S65-RPR-0520-S	S65-RPB-0520-S	S65-RPC-0520-S	1-7/16"	7.3
		500	Signature	6-1/2"		S65-SWB-0520-S		1-7/16"	8
		650	Polyolefin	6-1/2"	S65-POR-0520-S	S65-POB-0520-S	S65-POC-0520-S	1-7/16"	8.7
		750	Urethane Polypropylene	6-1/2"	S65-UPR-0520-S	S65-UPB-0520-S	S65-UPC-0520-S	1-7/16"	7.3
		800	Rubber on Aluminum-EHT	6-1/2"		S65-RAB-0520-S-EHT		1-7/16"	8.6
		1000	Durastan	6-1/2"	S65-DUR-0520-S	S65-DUB-0520-S	S65-DUC-0520-S	1-7/16"	9
		1000	High Temp Nylon	6-1/2"	S65-HNR-0520-S			1-7/16"	9
		1000	Solid Urethane	6-1/2"		S65-MUB-0520-S		1-7/16"	9
		1050	Urethane on Aluminum	6-1/2"	S65-UAR-0520-S		S65-UAC-0520-S	1-7/16"	8.5
		1050	Urethane on Iron	6-1/2"	S65-UIR-0520-S	S65-UIB-0520-S	S65-UIC-0520-S	1-7/16"	9
		1200	GT	6-1/2"		S65-GTB-0520-S		1-7/16"	9
6"	2"	525	Performance TPR	7-1/2"	S65-RPR-0620-S	S65-RPB-0620-S	S65-RPC-0620-S	1-5/8"	7.7
		600	Signature	7-1/2"		S65-SWB-0620-S		1-5/8"	9
		700	Polyolefin	7-1/2"	S65-POR-0620-S	S65-POB-0620-S	S65-POC-0620-S	1-5/8"	8.7
		820	Rubber on Aluminum-EHT	7-1/2"		S65-RAB-0620-S-EHT		1-5/8"	10
		900	Urethane Polypropylene	7-1/2"	S65-UPR-0620-S	S65-UPB-0620-S	S65-UPC-0620-S	1-5/8"	7.7
		1000	Omega	7-1/2"	S65-UOR-0620-S	S65-UOB-0620-S	S65-UOC-0620-S	1-5/8"	12
		1200	Durastan	7-1/2"	S65-DUR-0620-S		S65-DUC-0620-S	1-5/8"	10
		1200	GT	7-1/2"		S65-GTB-0620-S		1-5/8"	10
		1200	High Temp. Nylon	7-1/2"	S65-HNR-0620-S	S65-HNB-0620-S		1-5/8"	10
		1200	Solid Urethane	7-1/2"		S65-MUB-0620-S		1-5/8"	10
		1200	Urethane on Aluminum	7-1/2"	S65-UAR-0620-S		S65-UAC-0620-S	1-5/8"	11
		1200	Urethane on Iron	7-1/2"	S65-UIR-0620-S	S65-UIB-0620-S	S65-UIC-0620-S	1-5/8"	12
		8"	2"	600	Performance TPR	10-1/8"	S65-RPR-0820-S	S65-RPB-0820-S	S65-RPC-0820-S
700	Signature			10-1/8"		S65-SWB-0820-S		2-3/8"	10
800	Polyolefin			10-1/8"	S65-POR-0820-S	S65-POB-0820-S	S65-POC-0820-S	2-3/8"	9.1
1000	Rubber on Aluminum-EHT			10-1/8"		S65-RAB-0820-S-EHT		2-3/8"	11
1000	Urethane Polypropylene			10-1/8"	S65-UPR-0820-S	S65-UPB-0820-S	S65-UPC-0820-S	2-3/8"	9.1
1200	Durastan			10-1/8"	S65-DUR-0820-S	S65-DUB-0820-S	S65-DUC-0820-S	2-3/8"	11
1200	GT			10-1/8"		S65-GTB-0820-S		2-3/8"	11
1200	Omega			10-1/8"	S65-UOR-0820-S	S65-UOB-0820-S	S65-UOC-0820-S	2-3/8"	13
1200	Solid Urethane			10-1/8"		S65-MUB-0820-S		2-3/8"	11
1200	Urethane on Aluminum			10-1/8"	S65-UAR-0820-S		S65-UAC-0820-S	2-3/8"	12
1200	Urethane on Iron			10-1/8"	S65-UIR-0820-S	S65-UIB-0820-S	S65-UIC-0820-S	2-3/8"	13

To order a rigid caster, change the "S" to "R" in the model number. For example: "S65-GTB-0420-R". To order a rig only, omit the blue letters. For example: "S65-0420-S". Dimensions shown are nominal. If precise dimensions are required, consult your RWM representative. For approximate weight of our rigid caster, deduct 5.4 pounds.